Satisfy Professional's Needs



18Vx2 LXT 14" Portable Cut-Off Saw DLW140

World's First Cordless Portable Cut-off (as of Cotober 1, 2018)

THE REAL

IRV



2-15/16" x 1-3/4", T: 20 ga metal stud with BL1850B x 2









Toolless replacement of abrasive cut-off wheel



Electric brake

Quick release vise





Cutting Capacity

A workpiece thinner than 1.6 mm is recommended for cutting with this tool.

Miter	angle	
0 °	45°	
D : ø127mm (5″)	D : ø127mm (5″)	
H x W : 115 x 130 (4-1/2"x5-1/8") 102 x 194mm (4"x 7-5/8") 70 x 233mm (2-3/4"x 9-1/8")	H x W : 115 x 103mm (4-1/2"x 4-1/16")	
H x W: 119 x 119mm (4-11/16″x 4-11/16″)	H x W: 106 x 106mm (4-3/16″x 4-3/16″)	
S x S : 137 x 137mm (5-3/8″x 5-3/8″)	S x S : 100 x 100mm (4″x 4″)	
	0° D: Ø127mm (5″) H x W: 115 x 130 (4-1/2″x5-1/8″) 102 x 194mm (4″x 7-5/8″) 70 x 233mm (2-3/4″x 9-1/8″) H x W: 119 x 119mm (4-11/16″x 4-11/16″) S x S: 137 x 137mm	

D: Diameter W: Width H: Height S : Side



Carry handle for easy transport to job site



Large spark guard







makes it easy to lock down the saw head for storage and transport.

Accessory Abrasive cut-off wheel For Steel Studs, Ferrous Metals Size: 14" x 7/64" x 1"

Grit : A36P-BF Part No. B-64705



Battery Capacities Blade Diameter Arbor No Load Speed Cutting Capacity: **Overall Length**

Two 18V Li-Ion 14" (355 mm) 1" (25.4 mm) 3,800 RPM

45 Degrees: 5" (127 mm) 90 Degrees: 5" (127 mm) 21-1/8" (537 mm)

Standard Equipment: 14" Abrasive Wheel (1 Ea. B-64705-5), Vise (135708-8)



🕅 🖉 Brake

Soft Start

makita.ca

Load status indicator



As the motor load increases, the lighting lamp increases.

Toolless adjustment of guide plate



allows for easy adjustment of the guide plate by simple handling • 3 stage position change

• 0 to 45 degree angle adjustment

Saw head locking by pin lock