

Wide range of accessories available for various applications

Cutting (plunge cutting)



Applications:
Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

Benefits:

- Different from jig saws, etc, able to make a plunge cut in the wall for electrical connection box, lighting, exhaust fan, etc.
- The blade can be positioned in twelve different angles to allow easy operation in tight spaces.

Cutting



Applications:
Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

Benefits:

- Able to perform long distance push cut.
- The segment shape allows flush cutting.

Sanding



Applications:
Wood sanding, concrete sanding, or paint removal, etc. with a variety range of abrasive papers.

Benefits:

- Able to sand in corners.
- Connectable to vacuum cleaner with optional dust extraction system.

Removing grout/ Cutting tiles



Applications:
Replacing broken wall or floor tile.

Benefits:

- Less amount of dust scattering thanks to oscillating action.
- The segment shape allows flush cutting.

Scraping



Applications:
Removing mortar, tile adhesive, hardened glue, window putty, caulking, paint, etc.

Benefits:
Low-profile blade with a narrow tip allows easy removal of caulking, window putty, etc.

Multi Tool TM3000CX1



Strokes Per Minute	6,000 - 20,000 SPM
Oscillation Angle	3.2°
AMPS (120V)	3.0 A
Overall Length	10-7/8" (275 mm)

- Double insulation
- Variable Speed
- Constant Speed
- Soft Start

When QUALITY & SERVICE COUNTS – Choose Makita

makita.ca



Multi Tool TM3000CX1



EXTRA VERSATILE

Wide selection of accessories available for various applications

Oscillating Multi Tool



Compatible with all OIS (Oscillating Interface System) accessories



The standard equipment may vary by country.



Cutting PVC, FRP pipes



Cutting metals



Wood flush cutting



Wood plunge cutting



Deep plunge cutting



Sanding and polishing various materials



Cutting tiles



Removing mortar, tile adhesive

High operation efficiency

Oscillations per minute: up to 20,000 min⁻¹
Oscillating angle: 3.2°

Soft start

allows accurate landing of the blade on the surface of workpiece in various applications.

Constant speed control



Multi angle setting



Fully 360° multi angle setting enables users to position accessories in 12 different angles (each 30°) to allow access to tight spaces for optimum maneuverability.

Dust extraction system (Option)



Dust extraction system is available as an option for aggressive dust removal in applications with sanding pad.

Items of standard equipment may vary by country or area.



Cutting plasterboards



Metal flush cutting



Flush cutting of nails



Routing joints on wall tiles



Corner cutting



Cutting window putty, silicone



Cutting polystyrene, rubber



Scraping floor tiles